

کد فرم: G-QMS-F-016

«

»

/ /

()

.....

(.....)

.....

.....

.

:

()

.

:

().

:

.....

.....

()

:

∴ _____ ∴

∴ _____ ∴

∴ _____ ∴

∴ _____ ∴

∴ _____

∴ _____ ∴

(%)

: _____ :

: _____ :

: _____ :

∴ _____

∴ _____

∴ _____

∴ _____

∴

∴

∴

:

"

"

:

:

:

Y

:

:

() $\frac{\vdots}{\vdots}$

$\frac{\vdots}{\vdots}$

$\frac{\vdots}{\vdots}$

.....
"

$\frac{\vdots}{\vdots}$

:()

.()

.()
()

).

(.

.....

.....
.....

	Diode Set Manufacturer: SEMIKRON -A200	
	Diode Module No. 2950103 -A301	
	Module no. 2947815 -A302	
	Module no. 2947816 -A304	
	MMC-SICOMP Munting Rack CR 930 FOR FM486 , Module Location and 2X IM IO6 Including Power Supply For 24 VDC, -D0	
	MMC-SICOMP Function Module for FM486 for use in CR930 with 64-Pole Plug, including SW "BD486 Comnet" -D1	
	MMC-SICOMP IM IO6 Input / Output Module for FM 486 16 BO, 32 BI, 8 AO, 8 AI -D2	
	DC Isolating Amplifiers Fa. Knick -G205	
	DC Transducer -G700,-G701	
	Simovert Master Drives Output Choke Fmax=120HZ, FP=3 KHZ, 3-PH. 208 to 230V 44.2A -L100	
	Diode Failure Monitor 2 SEP, 32 Pole, ±15V, ±15A, +24V, 15MA -N308	
	Circuit Breaker 4.5 ... 6.3 A, N-Release 76 A, Size S00, Motor Protection, Class 10, Screw Connection -Q101	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 25 A -Q102	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 20 A -Q103	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 16 A -Q150	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 6 A -Q200,201	

	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic Single-Pole, 4A -Q203,206	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 1 A -Q160,205	
	N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 3 A -Q601	
	Metaloxide Varistor SLOV-B60K385 -R103	
	Shunt Rated Current 40A/150 MV -R104	
	Resistor 2.2 K OHM -R302	
	Resistor 220 OHM R302.1	
	Potentiometer 10K, 0.75W -R304	
	Position Switch Enclosed in moulded-Plastic Houseing 30mm Snap Action Contacts 1NO+1NC Overtravel Plunger -S150	
	Transformer with Disconnected Windings Power 2.5 KVA PRIM. Voltage 3*410 V Sec. Voltage 220 V Untapped Windings Frequency 50 HZ Vectorgroup YY0 Degree of Protection 1P00-T101 Terminals for Exterminal Connection	
	Votage Transformer 110V/5V/5V; 50 HZ-T301,302,303	
	Simovert VC Compact Unit / IP20, 3-PH. 208 to 230V, 50/60HZ, 44.2 A, L20=OPER. W. Unearthed Network (TI-Network) .For Converters of Type of Construction A to H -U100	
	DC /DC-CONVERTER Input: 125V DC Output: 200V DC Power: 2KW Voltage output adjustable with failure signal Manufacturer: KACO -U102	

	Undervoltage Relay -U103	
	Simovvert Master Drives Breaking Unit / IP 20, 280 to 310 VDC, 5 KW -U110	
	SIMEAS-AFM Transducer for electrical, quantities in power systems, customer parameterization using windows-software aux. power supply DC 24-to-60V -U305	
	Optocoupler order no. 2912183 -U601	
	Terminal Relay -X2:K1	
	Digitals Motorized Potentiometer U307, 24 VDC Auxiliary Voltage -Y301	
	Plug in order no. 2960818 -X150	
	Mechanical Latching Block for mounting onto 3TF3, 3TH30, AC and DC, 40 to 60 Hz, 24V -K202,203	
	SURGE SUPPRESSOR RC ELEMENT WITH WIRE SPACER AC 24 TO 48V/DC 24 TO 70V F.MOUNTING TO THE COIL TERMINAL FOR CONTACTORS SIZE 0 TO 2 -K202,203	
	AUXILIARY CONTACT BLOCK WITHOUT POSITION INDICATION FOR PLUGGING ONTO CONTACTORS 1NO -K202,203	
	AUXIL.SWITCH ,LATERALLY FITT.1NO + 1NC, F.CIRCUIT - BREAKERS, SIZE S00 -Q101	
	AUXIL , CONTACT CAN BE MOUNTED ON 1NO+1NC , FOR 5SX2+4+5 N-TYPE MINIAT.CIRCUIT - BREAKER -Q102;103	
	TERMINAL RELAY SOCKET -U601,A721/2	
	TERMINAL RELAY SOCKET -X2:-X5	
	CABLE X3.1	
	CABLE -X4.1	

G-QMS - F - 020/00 :

“

”

.....

/

		()	
	():		

:

.....

.....

.

:

:

:

:

« »

()	()			
			Diode Set Manufacturer: SEMIKRON	
			-A200	
			Diode Module No. 2950103	
			-A301	
			Module no. 2947815	
			-A302	
			Module no. 2947816	
			-A304	
			MMC-SICOMP Munting Rack CR 930 FOR FM486 , Module Location and 2X IM IO6 Including Power Supply For 24 VDC,	
			-D0	
			MMC-SICOMP Function Module for FM486 for use in CR930 with 64-Pole Plug, including SW "BD486 Comnet"	
			-D1	
			MMC-SICOMP IM IO6 Input / Output Module for FM 486 16 BO, 32 BI, 8 AO, 8 AI	
			-D2	
			DC Isolating Amplifiers Fa. Knick	
			-G205	
			DC Transducer	
			-G700,-G701	
			Simovert Master Drives Output Choke Fmax=120HZ, FP=3 KHZ, 3-PH. 208 to 230V 44.2A	
			-L100	
			Diode Failure Monitor 2 SEP, 32 Pole, ±15V, ±15A, +24V, 15MA	
			-N308	
			Circuit Breaker 4.5 ... 6.3 A, N-Release 76 A, Size S00, Motor Protection, Class 10, Screw Connection	
			-Q101	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 25 A	
			-Q102	

()	()			
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 20 A -Q103	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 16 A -Q150	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 6 A -Q200,201	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic Single-Pole, 4A -Q203,206	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 1 A -Q160,205	
			N-Type AC/DC MIN. CIRC. -BREAKER 380V, DC 220V, 4,5KA, C Characteristic 2-Pole, 3 A -Q601	
			Metaloxide Varistor SLOV-B60K385 -R103	
			Shunt Rated Current 40A/150 MV -R104	
			Resistor 2.2 K OHM -R302	
			Resistor 220 OHM R302.1	
			Potentiometer 10K, 0.75W -R304	
			Position Switch Enclosed in moulded-Plastic Houseing 30mm Snap Action Contacts 1NO+1NC Overtravel Plunger -S150	
			Transformer with Disconnected Windings Power 2.5 KVA PRIM. Voltage 3*410 V Sec. Voltage 220 V Untapped Windings Frequency 50 HZ Vectorgroup YY0 Degree of Protection 1P00-T101 Terminals for Exterminal Connection	

()	()			
			Votage Transformer 110V/5V/5V; 50 HZ-T301,302,303	
			Simovert VC Compact Unit / IP20, 3-PH. 208 to 230V, 50/60HZ, 44.2 A, L20=OPER. W. Unearthed Network (TI-Network) .For Converters of Type of Construction A to H -U100	
			DC /DC-CONVERTER Input: 125V DC Output: 200V DC Power: 2KW Voltage output adjustable with failure signal Manufacturer: KACO -U102	
			Undervoltage Relay -U103	
			Simovert Master Drives Breaking Unit / IP 20, 280 to 310 VDC, 5 KW -U110	
			SIMEAS-AFM Transducer for electrical, quantities in power systems, customer parameterization using windows-software aux. power supply DC 24-to-60V -U305	
			Optocoupler order no. 2912183 -U601	
			Terminal Relay -X2:K1	
			Digitals Motorized Potentiometer U307, 24 VDC Auxiliary Voltage -Y301	
			Plug in order no. 2960818 -X150	
			Mechanical Latching Block for mounting onto 3TF3, 3TH30, AC and DC, 40 to 60 Hz, 24V -K202,203	
			SURGE SUPPRESSOR RC ELEMENT WITH WIRE SPACER AC 24 TO 48V/DC 24 TO 70V F.MOUNTING TO THE COIL TERMINAL FOR CONTACTORS SIZE 0 TO 2 -K202,203	
			AUXILIARY CONTACT BLOCK WITHOUT POSITION INDICATION FOR PLUGGING ONTO CONTACTORS 1NO -K202,203	
			AUXIL.SWITCH ,LATERALLY FITT.1NO + 1NC,	

()	()			
			F.CIRCUIT - BREAKERS, SIZE S00 -Q101	
			AUXIL , CONTACT CAN BE MOUNTED ON 1NO+1NC , FOR 5SX2+4+5 N-TYPE MINIAT.CIRCUIT - BREAKER -Q102;103	
			TERMINAL RELAY SOCKET -U601,A721/2	
			TERMINAL RELAY SOCKET -X2:-X5	
			CABLE X3.1	
			CABLE -X4.1	

" ..

:

" "

()

:

" "

()

()

()

()

%

" "

:

$$C = L \times \frac{C}{(i \times (100-t)) - 100}$$

()

//

%

"
